



SEALERS/FINISHES



SEALER FINISH

TECHNICAL DATA SHEET

PACKAGING	CODE
4 x 4 L (4 x 1.06 US gal)	2397278001
20 L (5.28 US gal)	2397334001

DESCRIPTION:

EP80 Sealer Finish is designed with the newest in environmentally preferable polymer technology. It does not contain zinc or other heavy metals to interfere with industrial wastewater treatment processes. The gloss, durability, recoatability and removability of EP80 are excellent. It dries to a smooth, hard, clear and colourless coating in 30 minutes under almost any condition. Excellent for vinyl composition, linoleum, sheet vinyl, concrete, terrazzo, quarry, Mexican tile and most resilient type flooring.

USE DIRECTIONS:

NOTE: Ensure adequate ventilation. Floor surface must be clean, dry and free of residue prior to applying EP80. When stripping is required, choose a Green Seal® certified floor stripper.

APPLYING AS A SEALER OR SEALER/FINISH:

- 1) On a stripped floor, apply 3-5 coats of EP80 with a clean synthetic finish mop or a microfiber mop or applicator system.
- 2) Allow each coat to dry completely, normally 30 minutes before recoating.
- 3) Apply additional coats depending on gloss expectations and traffic conditions.

PRECAUTIONS FOR FOOD PLANTS:

Must be applied in keeping with manufacturers' recommendations for application on hard smooth level surfaces. To avoid possible adverse organoleptic effects in food, which are processed in the area, adequate precautions should be taken to ensure that the volatile constituents of the applied products do not contaminate the foods.

RECYCLING:

This product including the container, label and shipping carton are all designed to be recycled. Follow all Federal, Provincial and local regulations regarding waste disposal.

Surfactants in this product are readily biodegradable in accordance with OECD 301 standard.

SECURITY:

HEALTH	1
FLAMMABILITY	0
REACTIVITY	0
PERSONAL PROTECTION	X
X =	See SDS
0 =	Insignificant
1 =	Slight
2 =	Moderate
3 =	High
4 =	Extreme

NOTE:

The data presented herein is based on experiments and information believed reliable. However, we can make no guarantee on performance of, or results obtained through the use of the product herein described owing to varying conditions in laboratories and plants over which we have no control. Neither can any guarantee be given that the products or uses outlined will not infringe any existing patents.

TECHNICAL SPECIFICATIONS:

Appearance	Opaque Liquid
Colour	White
Odour	Acrylic Odour
Specific Gravity	1.003 – 1.043
pH	6.5 – 9.0
Refractive Index (% Brix)	22.0 – 26.0%
4 L (1.06 US Gallon) Coverage	139 – 186 m ² (1500 – 2000 ft ²)



PRODUCT CERTIFIED FOR REDUCED ENVIRONMENTAL IMPACT. VIEW SPECIFIC ATTRIBUTES EVALUATED: UL.COM/EL
 PRODUCT CERTIFIÉ À IMPACT ENVIRONNEMENTAL RÉDUIT. VÉRIFIEZ LES ATTRIBUTS ÉVALUÉS: UL.COM/EL



* This product meets Green Seal® Standard GS-40 based on effective performance and protective limits on VOCs and human & environmental toxicity. GreenSeal.org.

** Floor coating and finishing material, as to slip resistance only.

FOR A MORE COMPLETE CLEAN, CONTACT US!

AVMOR Ltd.
 950 Michelin, Laval, Québec Canada H7L 5C1
 Tel.: (450) 629-3800 Fax: (450) 629-4355
 1 800 387-8074 support@avmor.com

avmor.com



Let's
CLEAN

TRAINING
 PROGRAMS
 AVAILABLE