



FINISHES

HIGH SOLIDS NANO POLYMER FINISH

TECHNICAL DATA SHEET

PACKAGING	CODE
4 x 3.78 L (4 x 1 US gal)	243127001
18.9 L (5 US gal)	2431332001

DESCRIPTION:

NF322 High Solids Nano Polymer Floor Finish is ideal for limited maintenance environments such as classrooms, patient rooms, offices and elevators. It also responds well to occasional burnishing – making it suitable for retail establishments, hallways and other frequently maintained areas. Benefits speak for themselves:

Performance

- Exceeds traditional gloss readings (> 90°)
- Long lasting deep gloss
- High durability
- Consistent gloss build per coat
- Resists black marking, scuffing and soil penetration

Safety & Convenience

- Fast-drying, 15-20 minutes under normal conditions
- UL-classified (slip-resistant)
- Low emissions formula (< 1% VOC's)
- Ammonia-free for dramatically reduced odor
- Detergent resistant

USE DIRECTIONS:

APPLICATION:

For best results, apply a maximum of 4 coats in 24 hours.

- 1) Remove the old floor finish completely using an Avmor floor stripper and rinse thoroughly with water.
- 2) Once the floor is dry, with clean equipment, apply thin even coats of finish.
- 3) Under normal conditions, allow to dry for 15-20 minutes between coats.

MAINTENANCE:

- 1) Dust mop the floor to remove dirt and grit.
- 2) Use *SF152 Cleaner and Gloss Enhancer* following product use directions, with mop or autoscrubber to remove soil.
- 3) When required use a burnisher (1500-3000 RPM), burnish the floor with a natural blend pad to build shine, remove scratches, scuff marks or repair high traffic areas.

PRECAUTIONS FOR FOOD PLANTS:

Must be applied in keeping with manufacturers' recommendations for application on hard smooth level surfaces. To avert possible adverse organoleptic effects in food, which are processed in the area, adequate precautions should be taken to ensure that the volatile constituents of the applied products do not contaminate the foods.

RECYCLING:

This product package including the container, label and shipping carton are all designed to be recycled. Follow all Federal, Provincial and Local regulations regarding waste disposal.

SECURITY:

HEALTH	1
FLAMMABILITY	0
REACTIVITY	0
PERSONAL PROTECTION	X
X =	See SDS
0 =	Insignificant
1 =	Slight
2 =	Moderate
3 =	High
4 =	Extreme

NOTE:

The data presented herein is based on experiments and information believed reliable. However, we can make no guarantee on performance of, or results obtained through the use of the product herein described owing to varying conditions in laboratories and plants over which we have no control. Neither can any guarantee be given that the products or uses outlined will not infringe any existing patents.

TECHNICAL SPECIFICATIONS:

Appearance	Translucent liquid
Colour	White
Odour	Characteristic
pH	7.0 – 8.1
Refractive Index (% Brix)	26.0 – 28.0%
Solids	22.0%
Maximum VOC Content	< 1%
US Gallon (3.78 L) Coverage	3000 ft ² (279 m ²)



* Floor Coating and Finishing Material. As to Slip Resistance Only. 177S



FOR A MORE COMPLETE CLEAN, CONTACT US!

AVMOR Ltd.
950 Michelin, Laval, Québec Canada H7L 5C1
Tel.: (450) 629-3800 Fax: (450) 629-4355
1 800 387-8074 support@avmor.com

avmor.com



Let's
CLEAN®

TRAINING
PROGRAMS
AVAILABLE